



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 3SKB Rolling Series

3SKB-R10U20W

Specifications

Lid Depth	3.25 in	8.26 cm
Interior Length	TBA	TBA
Interior Width	19.00 in	48.26 cm
Interior Height	17.50 in	44.45 cm
Interior Cu. Volume	3.85 cu ft	0.11 cu m
Space Units Total	10	10
Rackable Depth	20.00 in	50.80 cm
Depth Front Rail to Back Lid	23.25 in	59.06 cm
Exterior Depth	TBA	TBA
Exterior Width	TBA	TBA

Exterior Height	TBA	TBA
Exterior Cu. Volume	13.10 cu ft	0.37 cu m
Carton Length	TBA	TBA
Carton Width	TBA	TBA
Carton Depth	TBA	TBA
Carton Cu. Volume	TBA	TBA
Product Weight	59.00 lb	26.76 kg
Shipping Weight	67.00 lb	30.39 kg
Color	Black	Black

Description

The Rolling Shockmount Case series incorporates our black powder coated twist latches with locking loops and low profile injection molded pull handle with a 20 inch deep tough shell. The molded design provides extra stiffness in the lids and sides and allows for secure stacking. Rack depth front to rear rail is 20 inches and each lid is 2-1/4 inches deep. Rack rails are pre-threaded for standard 10-32 hardware and the mounting screws are included. Doors are fully usable even when racks are stacked together. Elastomeric shocks protect even the heaviest of loads. Sliding retractable handle, ambient pressure relief valve, oversized snap-down handles on each side, roller blade wheels, and gasket protected front and rear doors are all standard equipment.

Features

- Black powder coated twist latches with locking loops
- Threaded steel rails
- Rear rails
- Built-in wheels
- Shock and water resistant
- Low profile pull handle
- Mounting hardware is included

P.O. Box 936
Sykesville, MD 21784
www.SpecialtyCases.com

Phone: 301-497-9032
Toll Free: 800-267-1674

Last Updated
January 2023