



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

Pelican Air Protector Cases

1525WD

Specifications

Lid Depth	2 in	5.1 cm
Base Depth	4.75 in	12.1 cm
Total Depth	6.75 in	17.1 cm
Interior Length	20.50 in	52.1 cm
Interior Width	11.31 in	28.7 cm
Interior Depth	6.75 in	17.1 cm
Interior Cu. Volume	0.91 cu ft	25.77 cu dm
Exterior Length	21.96 in	55.8 cm
Exterior Width	13.97 in	35.5 cm
Exterior Depth	7.49 in	19 cm

Bouyancy	57.90 lbs	26.3 kg
Range Temperature	-60/160° F	-51/71° C
Weight with Foam	7.13 lbs	3.2 kg
Weight w/o Foam	5.99 lbs	2.7 kg
Wheels	n/a	

Body:	Proprietary Polypropylene Blend
Latch:	ABS
O-Ring:	EPDM
Purge Body:	ABS
Purge Vent:	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven
Purge O-Ring:	70 Shore Nitrile

Description

Pelican Air Protector Cases are the lightest premium case on the planet. They can be up to 40% lighter than other injection molded cases. There are 6 different sizes available with this new, high tech construction and all of them have the same Pelican quality and performance. All of the Air cases are waterproof, dustproof and crushproof, guaranteed.

Features

- Watertight, airtight, dustproof, chemical resistant and corrosion proof case
- Super-light proprietary HPX-2 Polymer
- Pad lockable with stainless steel protected hasps
- Easy open double throw latches
- Fold down, comfortable rubber over-molded handle
- Stainless steel hardware
- Automatic purge valve
- Business card holder
- Lifetime Warranty
- Interior Options: No Foam, Pick N Pluck Foam, Padded Dividers, TrekPak Dividers