SPECIALTY CASES

[DESIGN = SUPPORT = PROTECT]

Product Datasheet

Pelican Air Protector Cases

1605

Specifications

Lid Depth	2 in	5.1 cm	Bouyancy		112.90 lbs	51.2 kg
Base Depth	6.38 in	16.2 cm	Range Temperature		-60/160° F	-51/71° C
Total Depth	8.38 in	21.3 cm	Weight with Foam		11.61 lbs	5.3 kg
Interior Length	26 in	66 cm	Weight w/o Foam		9.28 lbs	4.2 kg
Interior Width	14 in	35.6 cm	Wheels		n/a	
Interior Depth	8.38 in	21.3 cm		Propri	otary Polypro	nylono
Interior Cu. Volume	1.77 cu ft	50.12 cu dm	Body:	Blend	ietary Polypropylene	
Exterior Length	28.87 in	73.3 cm	Latch:	ABS		
Exterior Width	16.77 in	42.6 cm	O-Ring:	EPDM		
Exterior Depth	9.12 in	23.2 cm	Purge Body:	ABS		
			Purge Vent:	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven		
			D 0 D			

Purge O-Ring: 70 Shore Nitrile

Description

Pelican Air Protector Cases are the lightest premium case on the planet. They can be up to 40% lighter than other injection molded cases. There are 6 different sizes available with this new, high tech construction and all of them have the same Pelican quality and performance. All of the Air cases are waterproof, dustproof and crushproof, guaranteed.

Features

- Watertight, airtight, dustproof, chemical resistant and corrosion proof case
- Super-light proprietary HPX-2 Polymer
- Pad lockable with stainless steel protected hasps
- Easy open double throw latches
- Fold down, comfortable rubber over-molded handle
- Stainless steel hardware
- Automatic purge valve
- Business card holder
- Lifetime Warranty
- Interior Options: No Foam, Pick N Pluck Foam, Padded Dividers, TrekPak Dividers

Last Updated January 2023 P.O. Box 936 Sykesville, MD 21784 www.SpecialtyCases.com

Phone: 301-497-9032 Toll Free: 800-267-1674