



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB Shallow Rack Series

1SKB-R3S

Specifications

Interior Length	TBA	TBA
Interior Width	19.00 in	48.26 cm
Interior Height	5.25 in	13.34 cm
Interior Cu. Volume	0.62 cu ft	0.02 cu m
Space Units Total	3	3
Rackable Depth	10.70 in	27.18 cm
Depth Front Rail to Back Lid	12.30 in	31.24 cm
Exterior Depth	16.20 in	41.15 cm
Exterior Width	22.40 in	56.90 cm
Exterior Height	7.40 in	18.80 cm

Exterior Cu. Volume	1.55 cu ft	0.04 cu m
Min. Temperature	0.00° F	-17.78° C
Carton Length	16.50 in	41.91 cm
Carton Width	23.00 in	58.42 cm
Carton Depth	8.40 in	21.34 cm
Carton Cu. Volume	1.84 cu ft	0.05 cu m
Product Weight	10.40 lb	4.72 kg
Shipping Weight	11.80 lb	5.35 kg
Color	Black	Black

Description

The re-designed Roto-molded Shallow Rack Cases meet the needs of musicians and pro audio/video engineers. The new design now has a full front and rear cover instead of a rear access panel for easy access. Both doors have a rubber gasket to keep water out of the case.

The Shallow Racks are roto-molded for strength and durability and feature a new exterior design with interlocking capabilities, recessed steel, Mil-Spec black twist latches, shock absorbing rubber feet and new heavy-duty flush handles. With the addition of rear rack rails and the new cover design, the depth on the new Roto-molded Shallow Racks has been extended to 10.7" from front to rear rail. Gear can now be mounted front and rear with the supplied rackmount clips.

Features

- Roto-molded for strength and durability
- Front and rear gasketed covers
- Interlocking stacking ribs
- Recessed latches
- Heavy-duty flushmount handles
- Shock absorbing rubber feet
- Rackmount hardware included for secure mounting front or rear