



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 3SKB Series

1SKB-R916U20

Specifications

| | | |
|------------------------------|------------|-----------|
| Lid Depth | 3.25 in | 8.26 cm |
| Interior Length | TBA | TBA |
| Interior Width | 19.00 in | 48.26 cm |
| Interior Height | 28.00 in | 71.12 cm |
| Interior Cu. Volume | 6.16 cu ft | 0.17 cu m |
| Space Units Total | 16 | 16 |
| Rackable Depth | 20.00 in | 50.80 cm |
| Depth Front Rail to Back Lid | 24.50 in | 62.23 cm |
| Exterior Depth | 29.00 in | 73.66 cm |
| Exterior Width | 27.25 in | 69.22 cm |

| | | |
|---------------------|-------------|-----------|
| Exterior Height | 36.60 in | 92.96 cm |
| Exterior Cu. Volume | 16.74 cu ft | 0.47 cu m |
| Carton Length | TBA | TBA |
| Carton Width | TBA | TBA |
| Carton Depth | TBA | TBA |
| Carton Cu. Volume | TBA | TBA |
| Product Weight | 76.00 lb | 34.47 kg |
| Shipping Weight | 84.00 lb | 38.10 kg |
| Color | Black | Black |

Description

An internal frame mounted on adjustable elastomer shock absorbers on all eight corners. These revolutionary shocks are designed to control the effects of shock and vibration on three axes. The "sway" space around the internal frame provides natural air conditioning -- very important for delicate equipment. Inner rack chassis depth is 20" rail to rail with pre-threaded rack rails for standard 10-32 hardware that is included. They are half the weight of the old wooden cases.

Features

- Includes rear rails, front and rear doors
- Adjustable elastomer shock technology
- Precise level of shock absorption for any load
- Molded handles provide an easy and secure grasping point
- Mounting hardware in the racks is easy with the provided hardware