



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 2R Series

2R4417-8B-L

Specifications

Lid Depth	3.13 in	7.94 cm
Base Depth	4.88 in	12.38 cm
Interior Length	44.25 in	112.40 cm
Interior Width	17.50 in	44.45 cm
Interior Depth	8.00 in	20.32 cm
Interior Cu. Volume	3.59 cu ft	0.10 cu m
Exterior Length	47.38 in	120.33 cm
Exterior Width	21.75 in	55.25 cm
Exterior Depth	9.5 in	18.73 cm
Exterior Cu. Volume	4.40 cu ft	0.12 cu m

Max. Temperature	180.00° F	82.22° C
Min. Temperature	-40.00° F	-40.00° C
Max. Buoyancy	224.00 lb	102.00 kg
Carton Length	47.50 in	120.65 cm
Carton Width	21.75 in	55.25 cm
Carton Depth	9.75 in	24.77 cm
Carton Cu. Volume	5.83 cu ft	0.17 cu m
Product Weight	26.30 lb	11.93 kg
Shipping Weight	36.00 lb	16.33 kg
Color	Black	Black

Description

These Mil-Standard cases were designed to meet the most demanding military specifications, they are roto-molded for strength and durability, airtight and water proof with solid stainless steel latches and hinges that will withstand the most demanding shipping conditions.

The 2R Mil-Std. Cases are molded of (LLDPE) polyethylene impact resistant / UV stabilized material and meet or exceed MIL-STD 810 and MIL-C-4150J specifications.

Features

- Dual layered foam for added protection
- Convenient, sturdy wheels
- Comfortable over-molded tow and carrying handle
- Powder coated stainless steel twist latches with locking hasps
- Waterproof and dust tight design (MIL-C-4150J)
- LLDPE Polyethylene impact resistant
- Resistant to UV, solvents, corrosion, fungus (MIL-STD-810F)
- Pressure relief / breather valves
- Resistant to impact damage (MIL-STD-810F)
- TSA recognized and accepted locks
- ATA Rated

P.O. Box 936
Sykesville, MD 21784
www.SpecialtyCases.com

Phone: 301-497-9032
Toll Free: 800-267-1674

Last Updated
January 2023