



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 2R Series

2R4909-5B-L

Specifications

Lid Depth	2.25 in	5.72 cm
Base Depth	3.25 in	8.26 cm
Interior Length	49.50 in	125.73 cm
Interior Width	9.00 in	22.86 cm
Interior Depth	5.50 in	13.97 cm
Interior Cu. Volume	1.42 cu ft	0.04 cu m
Exterior Length	52.13 in	132.40 cm
Exterior Width	13.00 in	33.02 cm
Exterior Depth	6.88 in	17.46 cm
Exterior Cu. Volume	2.70 cu ft	0.08 cu m

Max. Temperature	180.00° F	82.22° C
Min. Temperature	-40.00° F	-40.00° C
Max. Buoyancy	89.00 lb	41.00 kg
Carton Length	53.00 in	134.62 cm
Carton Width	13.25 in	33.66 cm
Carton Depth	7.13 in	18.10 cm
Carton Cu. Volume	2.90 cu ft	0.08 cu m
Product Weight	17.95 lb	8.14 kg
Shipping Weight	21.00 lb	9.53 kg
Color	Black	Black

Description

These Mil-Standard cases were designed to meet the most demanding military specifications, they are roto-molded for strength and durability, airtight and water proof with solid stainless steel latches and hinges that will withstand the most demanding shipping conditions.

The 2R Mil-Std. Cases are molded of (LLDPE) polyethylene impact resistant / UV stabilized material and meet or exceed MIL-STD 810 and MIL-C-4150J specifications.

Features

- Layered foam for added protection
- Cushioned rubber over-molded carrying handle
- Black powder coated stainless steel twist latches with locking hasps
- Waterproof and dust tight design (MIL-C-4150J)
- LLDPE Polyethylene impact resistant
- Resistant to UV, solvents, corrosion, fungus (MIL-STD-810F)
- Pressure relief / breather valves
- Resistant to impact damage (MIL-STD-810F)
- TSA recognized and accepted locks
- ATA Rated