



# SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 2R Series

2R5212-7B-L

## Specifications

Lid Depth	3.13 in	7.94 cm	Max. Temperature	180.00° F	82.22° C
Base Depth	4.88 in	12.38 cm	Min. Temperature	-40.00° F	-40.00° C
Interior Length	52.50 in	133.35 cm	Max. Buoyancy	184.00 lb	84.00 kg
Interior Width	12.13 in	30.80 cm	Carton Length	55.50 in	140.97 cm
Interior Depth	8.00 in	20.32 cm	Carton Width	16.25 in	41.28 cm
Interior Cu. Volume	2.95 cu ft	0.08 cu m	Carton Depth	10.00 in	25.40 cm
Exterior Length	15.63 in	39.69 cm	Carton Cu. Volume	5.22 cu ft	0.15 cu m
Exterior Width	9.50 in	24.13 cm	Product Weight	25.95 lb	11.77 kg
Exterior Depth	4.65 cu ft	0.13 cu m	Shipping Weight	32.00 lb	14.51 kg
Exterior Cu. Volume	4.40 cu ft	0.12 cu m	Color	Black	Black

## Description

These Mil-Standard cases were designed to meet the most demanding military specifications, they are roto-molded for strength and durability, airtight and water proof with solid stainless steel latches and hinges that will withstand the most demanding shipping conditions.

The 2R Mil-Std. Cases are molded of (LLDPE) polyethylene impact resistant / UV stabilized material and meet or exceed MIL-STD 810 and MIL-C-4150J specifications.

## Features

- Dual layered foam for added protection
- Convenient, sturdy wheels
- Comfortable over-molded tow and carrying handle
- Powder coated stainless steel twist latches with locking hasps
- Waterproof and dust tight design (MIL-C-4150J)
- LLDPE Polyethylene impact resistant
- Resistant to UV, solvents, corrosion, fungus (MIL-STD-810F)
- Pressure relief / breather valves
- Resistant to impact damage (MIL-STD-810F)
- TSA recognized and accepted locks
- ATA Rated

P.O. Box 936  
Sykesville, MD 21784  
[www.SpecialtyCases.com](http://www.SpecialtyCases.com)

Phone: 301-497-9032  
Toll Free: 800-267-1674

Last Updated  
January 2023