SPECIALTY CASES

[DESIGN = SUPPORT = PROTECT]

Product Datasheet

SKB iSeries

3i-1711-6

Specifications

Lid Depth	1.75 in	4.45 cm	Max. Temperature	180.00° F	82.22° C
Base Depth	4.25 in	10.80 cm	Min. Temperature	-69.00° F	-56.11° C
Interior Length	17.00 in	43.18 cm	Max. Buoyancy	43.00 lb	20.00 kg
Interior Width	11.50 in	29.21 cm	Carton Length	18.88 in	47.94 cm
Interior Depth	6.00 in	15.24 cm	Carton Width	14.50 in	36.83 cm
Interior Cu. Volume	0.68 cu ft	0.02 cu m	Carton Depth	7.50 in	19.05 cm
Exterior Length	18.25 in	46.36 cm	Carton Cu. Volume	1.19 cu ft	0.03 cu m
Exterior Width	13.79 in	35.03 cm	 Product Weight	6.01 lb	2.77 kg
Exterior Depth	6.81 in	17.30 cm	Shipping Weight	7.10 lb	3.22 kg
Exterior Cu. Volume	0.99 cu ft	0.03 cu m	 Color	Black	Black

Description

SKB iSeries injection molded waterproof cases are constructed of ultra highstrength polypropylene copolymer resin. Each case is waterproof and dust tight with a submersible design (IP67) that is resistant to corrosion and impact damage. Its molded-in hinge, patented "trigger release" latch system, comfortable, snapdown rubber over-molded cushion grip handle, secure stacking, and automatic ambient pressure equalization valve (MIL-STD 648C) all contribute to its military grade design. Resistant to UV, solvents, corrosion, and fungus per MIL-STD-810F.

Features

- Injection molded High impact strength, 2.8x stronger than our competition
- Lightweight Lighter than the competition
- Interior options available
- Field replaceable hardware Latches, handles, hinges and wheels
- \bullet Best latches in the industry Trigger latches, open quickly and easily with one finger operation
- TSA lock options Easy transportation through airport security
- 44 sizes and counting

Last Updated July 2020 P.O. Box 936 Sykesville, MD 21784 www.SpecialtyCases.com

Phone: 301-497-9032 Toll Free: 800-267-1674