SPECIALTY CASES

[DESIGN = SUPPORT = PROTECT]

Product Datasheet

SKB iSeries

3i-3019-12

Specifications

Lid Depth	2.00 in	5.08 cm	Max. Temperature	180.00° F	82.22° C
Base Depth	10.00 in	25.40 cm	Min. Temperature	-69.00° F	-56.11° C
Interior Length	30.50 in	77.47 cm	Max. Buoyancy	258.00 lb	117.00 kg
Interior Width	19.50 in	49.53 cm	Carton Length	34.25 in	87.00 cm
Interior Depth	12.00 in	30.48 cm	Carton Width	22.63 in	57.48 cm
Interior Cu. Volume	4.13 cu ft	0.12 cu m	Carton Depth	13.38 in	33.99 cm
Exterior Length	33.42 in	84.89 cm	Carton Cu. Volume	6.00 cu ft	0.17 cu m
Exterior Width	22.04 in	55.98 cm	Product Weight	23.50 lb	10.60 kg
Exterior Depth	12.87 in	32.69 cm	Shipping Weight	26.95 lb	12.22 kg
Exterior Cu. Volume	5.49 cu ft	0.16 cu m	Color	Black	Black

Description

SKB iSeries injection molded waterproof cases are constructed of ultra highstrength polypropylene copolymer resin. Each case is waterproof and dust tight with a submersible design (IP67) that is resistant to corrosion and impact damage. Its molded-in hinge, patented "trigger release" latch system, comfortable, snapdown rubber over-molded cushion grip handle, secure stacking, and automatic ambient pressure equalization valve (MIL-STD 648C) all contribute to its military grade design. Resistant to UV, solvents, corrosion, and fungus per MIL-STD-810F.

Features

- Injection molded High impact strength, 2.8x stronger than our competition
- Lightweight Lighter than the competition
- Interior options available
- Field replaceable hardware Latches, handles, hinges and wheels
- Best latches in the industry Trigger latches, open quickly and easily with one finger operation
- TSA lock options Easy transportation through airport security
- 44 sizes and counting

Last Updated July 2020 P.O. Box 936 Sykesville, MD 21784 www.SpecialtyCases.com

Phone: 301-497-9032 Toll Free: 800-267-1674