



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB iSeries

3i-4909-5

Specifications

Lid Depth	1.50 in	3.81 cm
Base Depth	3.50 in	8.89 cm
Interior Length	49.00 in	124.46 cm
Interior Width	9.00 in	22.86 cm
Interior Depth	5.00 in	12.70 cm
Interior Cu. Volume	1.28 cu ft	0.04 cu m
Exterior Length	50.35 in	127.89 cm
Exterior Width	11.54 in	29.31 cm
Exterior Depth	5.84 in	14.83 cm
Exterior Cu. Volume	1.96 cu ft	0.06 cu m

Max. Temperature	180.00° F	82.22° C
Min. Temperature	-69.00° F	-56.11° C
Max. Buoyancy	80.00 lb	37.00 kg
Product Weight	12.50 lb	5.67 kg
Shipping Weight	15.00 lb	6.80 kg
Color	Black	Black

Description

SKB iSeries injection molded waterproof cases are constructed of ultra high-strength polypropylene copolymer resin. Each case is waterproof and dust tight with a submersible design (IP67) that is resistant to corrosion and impact damage. Its molded-in hinge, patented "trigger release" latch system, comfortable, snap-down rubber over-molded cushion grip handle, secure stacking, and automatic ambient pressure equalization valve (MIL-STD 648C) all contribute to its military grade design. Resistant to UV, solvents, corrosion, and fungus per MIL-STD-810F.

Features

- Injection molded - High impact strength, 2.8x stronger than our competition
- Lightweight - Lighter than the competition
- Interior options available
- Field replaceable hardware - Latches, handles, hinges and wheels
- Best latches in the industry - Trigger latches, open quickly and easily with one finger operation
- TSA lock options - Easy transportation through airport security
- 44 sizes and counting