



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB iSeries

3i-5014-6

Specifications

Lid Depth	1.50 in	3.81 cm	Max. Temperature	180.00° F	82.22° C
Base Depth	4.50 in	11.43 cm	Min. Temperature	-69.00° F	-56.11° C
Interior Length	50.50 in	128.27 cm	Max. Buoyancy	159.00 lb	72.00 kg
Interior Width	14.50 in	36.83 cm	Carton Length	53.13 in	134.94 cm
Interior Depth	6.00 in	15.24 cm	Carton Width	17.25 in	43.82 cm
Interior Cu. Volume	2.54 cu ft	0.07 cu m	Carton Depth	7.00 in	17.78 cm
Exterior Length	53.04 in	134.72 cm	Carton Cu. Volume	3.71 cu ft	0.11 cu m
Exterior Width	16.98 in	43.13 cm	Product Weight	19.20 lb	8.71 kg
Exterior Depth	6.84 in	17.37 cm	Shipping Weight	21.40 lb	9.71 kg
Exterior Cu. Volume	3.56 cu ft	0.10 cu m	Color	Black	Black

Description

SKB iSeries injection molded waterproof cases are constructed of ultra high-strength polypropylene copolymer resin. Each case is waterproof and dust tight with a submersible design (IP67) that is resistant to corrosion and impact damage. Its molded-in hinge, patented "trigger release" latch system, comfortable, snap-down rubber over-molded cushion grip handle, secure stacking, and automatic ambient pressure equalization valve (MIL-STD 648C) all contribute to its military grade design. Resistant to UV, solvents, corrosion, and fungus per MIL-STD-810F.

Features

- Injection molded - High impact strength, 2.8x stronger than our competition
- Lightweight - Lighter than the competition
- Interior options available
- Field replaceable hardware - Latches, handles, hinges and wheels
- Best latches in the industry - Trigger latches, open quickly and easily with one finger operation
- TSA lock options - Easy transportation through airport security
- 44 sizes and counting