



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 3SKB Rolling Series

3SKB-R12U20W

Specifications

Lid Depth	3.25 in	8.26 cm
Interior Length	TBA	TBA
Interior Width	19.00 in	48.26 cm
Interior Height	21.00 in	53.34 cm
Interior Cu. Volume	4.62 cu ft	0.13 cu m
Space Units Total	12	12
Rackable Depth	20.00 in	50.80 cm
Depth Front Rail to Back Lid	23.25 in	59.06 cm
Exterior Depth	TBA	TBA
Exterior Width	TBA	TBA

Exterior Height	TBA	TBA
Exterior Cu. Volume	14.83 cu ft	0.42 cu m
Carton Length	29.00 in	73.66 cm
Carton Width	31.00 in	78.74 cm
Carton Depth	31.00 in	78.74 cm
Carton Cu. Volume	16.13 cu ft	0.46 cu m
Product Weight	67.95 lb	30.82 kg
Shipping Weight	75.00 lb	34.02 kg
Color	Black	Black

Description

The Rolling Shockmount Case series incorporates our black powder coated twist latches with locking loops and low profile injection molded pull handle with a 20 inch deep tough shell. The molded design provides extra stiffness in the lids and sides and allows for secure stacking. Rack depth front to rear rail is 20 inches and each lid is 2-1/4 inches deep. Rack rails are pre-threaded for standard 10-32 hardware and the mounting screws are included. Doors are fully usable even when racks are stacked together. Elastomeric shocks protect even the heaviest of loads. Sliding retractable handle, ambient pressure relief valve, oversized snap-down handles on each side, roller blade wheels, and gasket protected front and rear doors are all standard equipment.

Features

- Black powder coated twist latches with locking loops
- Threaded steel rails
- Rear rails
- Built-in wheels
- Shock and water resistant
- Low profile pull handle
- Mounting hardware is included