



# SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB iSeries

3i-2015-7B-C

## Specifications

Lid Depth	2.00 in	5.08 cm	Max. Temperature	180.00° F	82.22° C
Base Depth	5.50 in	13.97 cm	Min. Temperature	-69.00° F	-56.11° C
Interior Length	20.50 in	52.07 cm	Max. Buoyancy	87.00 lb	40.00 kg
Interior Width	15.50 in	39.37 cm	Carton Length	22.00 in	55.88 cm
Interior Depth	7.50 in	19.05 cm	Carton Width	18.50 in	46.99 cm
Interior Cu. Volume	1.38 cu ft	0.04 cu m	Carton Depth	8.50 in	21.59 cm
Exterior Length	22.27 in	56.57 cm	Carton Cu. Volume	2.00 cu ft	0.06 cu m
Exterior Width	17.98 in	45.67 cm	Product Weight	10.45 lb	4.74 kg
Exterior Depth	8.32 in	21.13 cm	Shipping Weight	13.00 lb	5.90 kg
Exterior Cu. Volume	1.93 cu ft	0.05 cu m	Color	Black	Black

## Description

SKB iSeries injection molded waterproof cases are constructed of ultra high-strength polypropylene copolymer resin. Each case is waterproof and dust tight with a submersible design (IP67) that is resistant to corrosion and impact damage. Its molded-in hinge, patented "trigger release" latch system, comfortable, snap-down rubber over-molded cushion grip handle, secure stacking, and automatic ambient pressure equalization valve (MIL-STD 648C) all contribute to its military grade design. Resistant to UV, solvents, corrosion, and fungus per MIL-STD-810F.

## Features

- Injection molded - High impact strength, 2.8x stronger than our competition
- Lightweight - Lighter than the competition
- Interior options - Empty, cubed, layered foam, padded dividers or custom foam
- Field replaceable hardware - Latches, handles, hinges and wheels
- Best latches in the industry - Trigger latches, open quickly and easily with one finger operation
- TSA lock options - Easy transportation through airport security
- 44 sizes and counting